TEEL SIDE BULK

A SK CENERAL DHAY ROX

AXLE 3500# Quality Dexter Axle Idler

COUPLER 2" Durable Atwood A-Frame Style

CROSS MEMBERS 3" x 2" x 3/16" Angle Iron

FENDERS 9" x 32" Rounded Steel

FLOOR Pressure Treated 2x8 Pine Wood Planks Expanded Metal may be substituted at

no additional charge.

FRAME 3" x 2" x 3/16" Angle Iron

JACK 2000# Top Wind Set Back Jack

LIGHTS All boxed-in LED lights.

PAINT Cleaned and prepared metal is primed with

High Performance Primer and then given two coats of quality oil based, AUTOMOTIVE GRADE,

anti-corrosion paint for an extra durable high

gloss finish that lasts.

PLUG 4-way plug with protective loom and

security brackets

SAFETY CHAINS 1/4" x 27" with S-Hook.

5200# capacity rating per chain.

STAKE POCKETS 2" x 4" Pockets. Two per side

TAIL GATE 1-1/2" x 1-1/2" Square Tubing

with expanded metal. Rear gate is

4ft tall with upright supports and two durable latches.

Folds down for easy ramp loading and is removable.

TONGUE Wrapped Tongue Complete. 4" Channel.

The 4" Channel Iron provides outstanding weight

distribution and stronger support for extra wide trailers.

TOP RAIL 2" x 2" x 1/8" Angle Iron

UPRIGHTS 2"x 2" x 1/8" Angle Iron

GILLESPIE COATINGS. INC.

SIDES 12GA Steel Sides 24" High Standard



N I SA N I I V

IS ALWAYS A WELCOME IDEA

Whatever the need, Stagecoach engineers will design and plan the perfect custom trailer solution

100% DOT COMPLIANT

